

Blakeley Construction Profiles Ltd sprayed roofline goods guarantee

Blakeley Construction Profiles Ltd guarantees the following properties of our paint coating for PVCu. This guarantee is effective from the date of application.

Adhesion

The paint used is guaranteed to adhere to virgin PVCu and polyester powder coating for 10 years. The substrate will have been cleaned and prepared, and the paint applied in accordance with the manufacturer's procedure at the time of processing the contract.

Weather Resistance/ Colour Fastness

The weathering properties of Blakeley Construction Profiles Ltd correspond with Grey Scale 3 or greater over a period of 5 years when measured by reference to EN2010.

This guarantee is subject to the following conditions:

- That the paint applied by Blakeley Construction Profiles Ltd is applied to a virgin PVCu or polyester powder coated substrate.
- That the paint applied by Blakeley Construction Profiles Ltd is cleaned when soiled or at intervals of not greater than three months, commencing at the date of installation.
- That the paint applied by Blakeley Construction Profiles Ltd coating is cleaned using either cold or warm tap water containing a mild detergent, applied by soft cloth or brush. Nothing harsher than a soft bristle brush should be used.
- Full documented and corroborative records of cleaning must be kept for the period of the guarantee.
- The significant surface shall be defined by the customer and is the part of the total surface which is essential to the appearance and serviceability of the item. Edges, deep recesses and secondary surfaces are not included in the significant surface. The organic coating on the significant surface shall not have any scratches through to the base metal. When the organic coating on the significant surface is viewed at an oblique angle of about 60° to the upper surface, none of the defects listed below shall be visible from a distance of 3 metres: excessive roughness, runs, blisters,

- inclusions, craters, dull spots, pinholes, pits, scratches or any other unacceptable flaws.
- The coating shall be of even colour and gloss level with good hiding power. When viewed on site, these criteria shall be fulfilled as follows for parts used outside: viewed at a distance of 5 m for parts used inside: viewed at a distance of 3 m

Exclusions

The following are excluded from the guarantee:

- Substrates that are not virgin PVCu or polyester powder coating (unless approved, in writing, by Blakeley Construction Profiles Ltd) and substrates that are defective.
- Damage caused by mechanical abrasion.
- Damage caused by solvents and chemicals, including chemical damage caused by pollution.
- Touch up materials and the areas coated by them.

Provisions of the Guarantee

In the case of the paint applied by Blakeley Construction Profiles Ltd coating being found to be defective, Blakeley Construction Profiles Ltd.'s liability shall be limited to rectification work deemed necessary. This work will only be carried out by organisations appointed by Blakeley Construction Profiles Ltd. No claims for consequential losses will be accepted.

Distortion or damage to profiles and panels, caused by heat absorption when the colour is changed, is not the responsibility of the paint manufacturer or Blakeley Construction Profiles Ltd.

This guarantee shall be valid only where the product, to which the paint is applied, is installed in premises situated in the United Kingdom.

The guarantee is given exclusively to Blakeley Construction Profiles Ltd.'s customer and is not transferable and may not be assigned.

This guarantee is subject only to the jurisdiction of English courts acting under English law. Statutory rights of the customer shall not be affected by this guarantee.

The contents of this guarantee shall override any condition in any contract made between Blakeley Construction Profiles Ltd and its customer so that the conditions, provisions and exclusions of the guarantee shall prevail.